



PLAN OF DOOR PANELS IN OPEN AND CLOSED POSITIONS.
NOTE - STACK CAN BE MOVED TO ANY POSITION ACROSS OPENING. IF SIDEROOM IS AVAILABLE, LEAVES CAN FOLD CLEAR OF THE OPENING.

LEAF COUNTS	MAX. HEIGHT	UPTO 5200mm HIGH	UPTO 8000mm HIGH
2 LEAVES	2300mm WIDE	2100mm WIDE	
4 LEAVES	4600mm WIDE	4150mm WIDE	
6 LEAVES	6850mm WIDE	6200mm WIDE	
8 LEAVES	9150mm WIDE	8250mm WIDE	

Jewellers

Specialist Doors

NOTES
INSIDE FACE OF HEAD BEAM AND SEALING FACE BETWEEN JAMBS TO BE FREE FROM FIXINGS / FITTINGS ETC.
HEAD BEAM MUST BE SUITABLE TO ACCEPT M10 FIXING BOLTS AND DESIGNED TO TAKE DOOR WEIGHT OF APPROX 20kg/m². MAXIMUM ALLOWABLE DEFLECTION UNDER WEIGHT OF DOOR = 8mm.
FLOOR MUST BE LOWER THAN THRESHOLD IN SHADED LEAF SWEEPING AREAS MARKED *****.

- OPTIONS (please tick if reqd)
- WINDOWS (MAX 2 PER LEAF)
- 680x370 EASIFIT D/G ACRYLIC VISION PANEL
- 680x500 D/G SECURITY VISION PANEL
- WICKET DOOR
- WICKET DOOR STD LEVER HARDWARE
- WICKET DOOR PANIC HARDWARE (TO BE FITTED IN END LEAF ONLY)
- LOCKING - FOR EACH PAIR OF LEAVES
- ESPAGNOLETTE BOLT

QUANTITY: SETS AS DRAWN
SETS OPPOSITE HAND

FINISH: EXTERNAL:

INTERNAL:

CONTRACTOR/CIENT

SITE

OPENING / DOOR REF.

DATE: DRAWN BY:
DRAWING No. OSP-F-1M-5101

OSPREY DOOR - FULLY FLOATING SINGLE BUNCH BETWEEN JAMBS

