



LEAF CONFIG.	MAX. HEIGHT	MAX DOOR SIZES (MAX 50m ²)		
		UPTO 4500mm HIGH	UPTO 5200mm HIGH	UPTO 6000mm HIGH
3 LEAVES		3300mm WIDE	n/a	n/a
4 LEAVES		4450mm WIDE	4450mm WIDE	4000mm WIDE
5 LEAVES		5550mm WIDE	n/a	n/a
6 LEAVES		6700mm WIDE	6700mm WIDE	6050mm WIDE
8 LEAVES		9000mm WIDE	9000mm WIDE	8100mm WIDE
10 LEAVES		11250mm WIDE	11250mm WIDE	10150mm WIDE

- NOTES
- HEAD BEAM MUST BE SUITABLE TO ACCEPT M12 FIXING BOLTS AND DESIGNED TO TAKE DOOR WEIGHT OF APPROX 20kg/m². MAXIMUM ALLOWABLE DEFLECTION UNDER WEIGHT OF DOOR - 8mm.
 - INSIDE SURFACE OF HEAD BEAM TO BE MINIMUM OF 180mm.
 - FLOOR MUST BE LOWER THAN THE THRESHOLD IN THE FOLDING AREA MARKED **** TO ALLOW LEAVES TO OPEN FREELY.

NUMBER OF DOORS

FINISH (specify material and colour)
 EXTERNAL SKIN:
 INTERNAL SKIN:

- OPTIONS (please tick or indicate qty reqd)
- VISION PANELS - SEE GLAZING LAYOUT DRAWING
- 680x390 PLASTIC EASIFIT
 - 400x600 ALUMINIUM FRAME
 - 400x1200 ALUMINIUM FRAME
 - 600x600 ALUMINIUM FRAME
 - 600x1200 ALUMINIUM FRAME

- WICKET DOOR (indicate in which panel)
- STANDARD LEVER HARDWARE*
 - EMERGENCY ESCAPE FURNITURE*

- LOCKING - for each pair of leaves
- LEVER OPERATED FLOOR BOLT* BETWEEN LEAVES 1&2

- CONTROLS
- EXTRA PUSH BUTTON
 - AUTO TIMED RETURN
 - SINGLE PUSH OPEN / CLOSE
 - MICROWAVE SENSOR - INSIDE
 - KEYSWITCH
 - RADIO CONTROL

- SAFETY EQUIPMENT
- SAFETY EDGE
 - TRAFFIC LIGHT
 - PHOTOCELL

* NOTE - WICKET DOORS AND FLOOR BOLTS WILL BE FITTED WITH AN ELECTRICAL INTERLOCK

SITE DETAILS

DOOR REFERENCE

DATE DRAWN BY
 DRAWING No. OSP-F1P-5105

OSPREY DOOR - ELECTRICALLY OPERATED, ONE-WAY